For floating Laminate flooring

3 IN 1 SOUNDBLOCK FOAM 19dB



SUBFLOOR TYPE & APPLICATION

- Residential applications
- Concrete

COMPATIBLE FLOORING

✓ Floating laminate flooring (planks)

DESCRIPTION

Material: recyclable polyethylene foam, freon-free, with closed-cell structure

Total weight: 0.2kg per m²

Total thickness: 3.0mm

ARTICLE NUMBER

Article code: 8267 000

Packaging: single roll - 1.2 x 16.7m (20m²)

Minimum order: 1 unit (= 1 roll)

MORE INFORMATION

. Tarkett website



High-performance acoustic insulation



- Provides high-impact sound reduction, to 19dB with 7mm laminate products
- Minimises drum-sound

Greater comfort



- Enhances living spaces by making them quieter
- Ensures greater comfort underfoot
- Works with **underfloor heating**

Superior durability and safety



- Consists of 3mm polyethylene foam with a closed-cell structure for improved long-term resistance
- **Contains no freon**, better for people and the environment

COORDINATED ACCESSORIES FOR LAMINATE FLOORINGS



Installation tape:

- designed for use with underlayers beneath laminate
- easy to use Article code: 8026 000



Large skirtings:

- perfect match with flooring design
- shock-resistant
 Article code: 8025___















I TARKOMFORT SELF-ADHESIVE I TARKOMFORT PRO I TARKOMFORT PREMIUM I ELAFONO I TARKOMOUSSE I STANDARD FOAM 18dB | 3 IN 1 SOUNDBLOCK FOAM 19dB | TARKOFOAM II | TARKOLEX II |



TARKO SOLUTIONS

Underlaye